



THE STA-DRI COMPANY

Manufacturers of Quality Products since 1944

MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS

DATE OF PREPARATION: JANUARY 1, 1999 PAGE 1 OF 3
MANUFACTURER: THE STA-DRI COMPANY
ADDRESS: 1572 ANNAPOLIS RD, ODENTON, MARYLAND 21113
TELEPHONE: (410) 551-9192 NIGHT: (410) 551-9192
EMERGENCY: (410) 551-9192 NIGHT: (410) 551-9192

SECTION I PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION: NA
PRODUCT CLASS: WATERPROOFING PAINT
TRADE NAME: STA-DRI WATERPROOF MASONRY PAINT - POWDER

HMIS INFORMATION: HEALTH: 1 REACTIVITY: 0
FLAMMABILITY: 0 PERSONAL PROTECTION EQUIP.:
HAZARD INDEX: 4=SEVERE 3=SERIOUS 2=MODERATE 1=SLIGHT 0=LEAST

SECTION II HAZARDOUS INGREDIENTS

---INGREDIENT--- % BY ACGIH OSHA VAPOR OTHER
MATERIAL DESCRIPTION CAS# WT. TLV PEL PRESSURE LIMITS
PPM PPM

CRYSTALLINE SILICA 14808-60-7 16.5 NE 0.1 NONE
CARCINOGENIC (IARC)
PORTLAND CEMENT 65997-15-1 60-68 NE 4.7 NONE
NE= NOT ESTABLISHED NA= NOT AVAILABLE

THIS PRODUCT CONTAINS PIGMENTS WHICH MAY BECOME A DUST NUISANCE
WHEN REMOVED BY ABRASIVE BLASTING, SANDING, OR GRINDING.

THIS PRODUCT CONTAINS ONE OR MORE REPORTED CARCINOGENS OR SUSPECTED
CARCINOGENS WHICH ARE NOTED NTP, IARC OR OSHA-Z IN THE OTHER LIMITS
RECOMMENDED COLUMN.

SECTION III PHYSICAL DATA

BOILING RANGE	HIGH	NA	DF	LOW	NA	DF
VAPOR PRESSURE		NA				
VAPOR DENSITY		NA				
EVAPORATION RATE		NA				
WEIGHT PER GALLON		NA				
% VOLATILE BY VOLUME		NA				
% VOLATILE BY WEIGHT		NA				
VOC		NA				

(301) 912-2880 Washington • (410) 551-9192 Baltimore
(800) 638-8085 Toll Free • (410) 551-7801 Fax

1572 Annapolis Road, Odenton, Maryland 21113-0040

THE STA-DRI COMPANY
MATERIAL SAFETY DATA SHEET PAGE 2 OF 3
STA-DRI WATERPROOF MASONRY PAINT - POWDER

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:	NA	DOT CATEGORY:	NA
FLASH POINT (TCC):	NA	F	
EXPLOSION LEVEL:	LOWER: NA	UPPER:	NA
EXTINGUISHING MEDIA:	NA		
SPECIAL FIRE FIGHTING PROCEDURES:	NA		
UNUSUAL FIRE AND EXPLOSION HAZARDS:	NONE		

SECTION V HEALTH HAZARD DATA

CRYSTALLINE SILICA WARNING: THE INTERNATIONAL ASSOCIATION FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED CRYSTALLINE SILICA (CS) AS A PROBABLE CARCINOGENIC FOR HUMANS (CLASS 2). THIS CLASSIFICATION IS BASED ON THE FINDINGS OF LABORATORY ANIMAL STUDIES THAT WERE CONSIDERED LIMITED FOR CARCINOGENICITY. CS HAS NOT BEEN CLASSIFIED AS A CARCINOGEN BY NTP OR OSHA. MATERIALS THAT CONTAIN QUARTZ OR CRYSTALLINE SILICA ARE: TALC, CLAY, CEMENT, MOCA AND PERLITE. PIGMENT DUST WOULD NOT NORMALLY BE ENCOUNTERED WHEN HANDLING A PACKAGED PAINT PRODUCT CONTAINING PRE-WETTED PIGMENT. PROPER RESPIRATORY EQUIPMENT SHOULD BE WORN WHEN SANDING A DRIED PAINT FILM DUE TO THE PRESENCE OF CS.

EFFECTS OF OVER EXPOSURE:

ACUTE: WET CEMENT CAN DRY THE SKIN AND CAUSE ALKALI BURNS.
CEMENT DUST CAN IRRITATE THE EYES AND UPPER RESPIRATORY SYSTEM.

CHRONIC: CEMENT DUST CAN CAUSE INFLAMMATION OF THE CORNEA.

FIRST AID: IRRIGATE EYES IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. WASH EXPOSED SKIN AREAS WITH SOAP AND WATER.

SECTION VI REACTIVITY DATA

STABILITY:	[] UNSTABLE	[X] STABLE
HAZARDOUS POLYMERIZATION:	[] MAY OCCUR	[X] WILL NOT OCCUR
HAZARDOUS DECOMPOSITION		
PRODUCTS:	NONE	
INCOMPATIBILITY (MATERIALS TO AVOID):	AVOID CONTACT WITH POWERFUL OXIDIZING AGENTS.	
CONDITIONS TO AVOID:	NONE	

THE STA-DRI COMPANY
MATERIAL SAFETY DATA SHEET PAGE 3 OF 3
STA-DRI WATERPROOF MASONRY PAINT ~ POWDER

SECTION VII SPILL AND LEAK PROCEDURE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: USE DRY CLEANUP METHODS THAT DO NOT DISPERSE THE DUST INTO THE AIR. AVOID BREATHING THE DUST. EMERGENCY PROCEDURES ARE NOT REQUIRED. WASTE DISPOSAL METHOD: MATERIAL CAN BE DISPOSED OF AS COMMON WASTE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VIII SAFE HANDLING AND USE INFORMATION

THE STA-DRI COMPANY TAKES NO RESPONSIBILITY FOR DETERMINING WHAT MEASURES ARE REQUIRED FOR PERSONAL PROTECTION IN ANY SPECIFIC APPLICATION. THE GENERAL INFORMATION GIVEN SHOULD BE USED WITH DISCRETION., PROTECTIVE EYEWEAR: IN DUSTY ENVIRONMENTS, THE USE OF NIOSH/MSHA APPROVED RESPIRATOR IS RECOMMENDED. EYE PROTECTION: IN DUSTY ENVIRONMENTS, THE USE OF TIGHT FITTING GOGGLES IS RECOMMENDED. VENTILATION: LOCAL EXHAUST CAN BE USED, IF NECESSARY, TO CONTROL AIRBORNE DUST LEVELS, HYGIENIC PRACTICES: WASH HANDS THOROUGHLY BEFORE EATING AND USING WASHROOM.

SECTION IX SPECIAL INSTRUCTIONS

STORING AND HANDLING INSTRUCTIONS: NONE
DO NOT TAKE INTERNALLY.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

THE ABOVE INFORMATION CONCERNS THIS PRODUCT AS CURRENTLY FORMULATED AND IS BASED ON INFORMATION AVAILABLE AT THIS TIME. THE ADDITION OF THINNERS, REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.
